

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 19; and S. 24, T23-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2459)

Set ¼ sec. post, from which
A Fir 12" dia., bears N.70°W., 26 lks. dist.
A Fir 12" dia., bears N.3°E., 36 lks. dist.

Douglas County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam, crew - For: J.H. Connon - Oct. 27, 1960 - C.S. File 52/57

Found - Orig. 12" now 24" Fir stump, N.70°W., 17.2 ft. I open and find good scribing "B".
Orig. 12" now 24" Fir, N.3°E., 23.6 ft., shows good scar. I do not open.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S
¼ S24 S19
R8W R7W
1960

New BT - 12" R.Fir bears S.80°W., 62.5 ft. scribed ¼ S24 CS BT.

Fd. and used in BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCSO records Vol. 32 Page(s) 13532)

Fd. and used in BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #987, surveyed July/Nov. 1979 - (DCSO records Vol. 42 Page(s) 16582)

Fd. OK, Feb. 1981 by L. Roberts - M 86-64