

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 12 & 24 of T23-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2459)

Set post cor. to secs. 18, 19, 13 and 24, from which
A Fir 15" dia., bears N.45°E., 17 lks. dist.
A Fir 11" dia., bears S.55°E., 43 lks. dist.
A Fir 28" dia., bears S.27°W., 30 lks. dist.
A Fir 4" dia., bears N.10°W., 10 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2560-61)

The sec.cor. which is a post 4" sq., mkd. T23S S18 on NE.; R7W S19 on SE.; R8W S24 on SW.; and S13 on NW. faces, with 3 notches on N. and S. edges, from which

A Fir 30" dia., bears S.27°W., 30 lks. dist. mkd. T23S R8W S24 BT.

The other bearing trees being gone, I marked new ones as follows:

A Fir 4" dia., bears N.38°E., 73 lks. dist. mkd. T23S R7W S18 BT.

A Maple 18" dia., bears S.29°E., 79 lks. dist. mkd. T23S R7W S19 BT.

A Fir 12" dia., bears N.42°W., 122 lks. dist. mkd. T23S R8W S13 BT.

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCSO records Vol. 32 Page(s) 13533)

The Sec. cor., perpetuated with an iron water pipe, 18" long, 2½" dia., firmly set 10" in the ground, from which the remains of an original bearing tree:

A Fir snag 32" dia., bears N.45°E., 17 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 23 S
R 8 W R 7 W
S 13 S 18
S 24 S 19
1964

from which new bearing trees:

A Fir 10" dia., bears N.34½°E., 27 lks. dist. mkd. T23S R7W S18 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T23-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Fir 8" dia., bears S.69½°E., 71 lks. dist. mkd. T23S R7W S19 BT.
A Fir 15" dia., bears S.71 3/4°W., 98 lks. dist. mkd. T23S R8W S24 BT.
A Fir 25" dia., N.70°W. 96 lks. dist. mkd. T23S R8W S13 BT
Deposit the water pipe alongside the iron post.
(No record found by DCSO of water pipe. Jan. 1997)

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #987, surveyed July/Nov. 1979 - (DCSO records Vol. 42 Page(s) 16583)

The Sec. Cor., monumented with an iron post 2½" dia., firmly set, projecting 4" above ground, with 1964 brass cap, from which the remains of the original bearing trees;
A Fir snag 32" dia., bears N.45°E., 17 lks. dist., no marks remaining.
and trees mkd. by Brooks and Peterson in 1964:
A Fir 15" dia., bears N.34½°E., 27 lks. dist. with healed blaze.
A Fir 15" dia., bears S.69½°E., 71 lks. dist. with healed blaze.
A Fir stump 17" dia., bears S.71 3/4°W., 98 lks. dist. with healed blaze.
A Fir 30" dia., bears N.70°W., 96 lks. dist., with healed blaze.
and a new bearing tree:
A Yew 11" dia., bears S.71 3/4°W., 116 lks. dist. mkd. T23S R8W S24 BT.

BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1336, Surveyed Aug/Oct. 1986 - (DCSO records Vol. 48 Page(s) 18279)

At the sec. cor., monumented with an iron post 2½" dia., firmly set, projecting 4" above ground with the 1964 brass cap, from which the remains of an original bearing tree;
A rotted Fir snag, size indeterminate, bears N.45°E., 17 lks. dist., no marks visible.
and the remains of bearing trees mkd. by Brooks and Peterson
A Fir 17" dia., bears N.34½°E., 27 lks. dist., with healed blaze.
A Fir 18" dia., bears S.69½°E., 71 lks. dist., with healed blaze.
A Fir stump, size indeterminate, bears S.71½°W., 98 lks. dist., no marks visible.
(Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T23-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A Fir 33" dia., bears N.70°W., 96 lks. dist., with healed blaze.
and a new bearing tree:
An Alder 11" dia., bears S.23 3/4°W., 77 lks. dist., mkd.
T23S R8W S24 BT.