

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; and S. 13, T23-8

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2459)

Set ¼ sec. post, from which
An Alder 6" dia., bears N.65°W., 10 lks. dist.
A Dogwood 5" dia., bears S.14°E., 15 lks. dist.

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCSO records Vol. 32 Page(s) 13533-34)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: ¼
S 13 S 18
T 23 S
R 8 W R 7 W
1964

from which
A W.Fir 15" dia., S.76°E., 35 lks. dist. mkd. ¼ S18 BT.
A Cedar 13" dia., S.35°W., 47 lks. dist. mkd. ¼ S13 BT.

BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1336, Surveyed Aug/Oct. 1986 - (DCSO records Vol. 48 Page(s) 18279-80)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
From this point, the ¼ sec. cor., erroneously positioned by Brooks and Peterson, bears N.78°33'E., 0.632 chs. dist., monumented with an iron post 2½" dia., firmly set projecting 4" above ground, with brass cap mkd. and witnessed as described in the official record.
I remove the iron post, destroy the marks on the bearing trees, and at the true corner point,
Reset the iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: ¼
S 13 S 18
T 23 S
R 8 W R 7 W
1986

from which
A Hemlock 24" dia., bears N.87½°E., 96 lks. dist. mkd. ¼ S18 BT.
A Fir 30" dia., bears N.60°W., 82 lks. dist. mkd. ¼ S13 BT