

PRIMARY CORNER DESCRIPTION Sec Cor for 6 & 7; 1 & 12, T23-8

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2457)

 Set a post for cor. to secs. 6, 7, 1 and 12, from which
 A White Oak 20" dia., bears N.70°E., 80 lks. dist.
 A White Oak 4" dia., bears S.35°W., 88 lks. dist.
 No other trees convenient to mark, raised mound with pits as per instructions.

J.W. Cole, Deputy - Wit: Lou Smick - For: Oliver Hines and Del Wetherly - Feb. 18, 1921 - Vol. 3 Page 89; Field Book 20 Page 28; C.S. File 1/20

 I renewed from the original bearing trees both of which were alive and standing. I set an Oak post 4"x4"x40". Also an Iron pipe, 1" x 30" for corner and marked a new tree:
 A W.Oak 10" dia., N.53°15'W., 29.0 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, Vernon "Ray" Tracy and J. Brady, crew - Dec. 1965 - C.S. File 52/125-30

 Found - Orig. 20" now 30" W.Oak N.70°E., 52.8 ft., chopped open approx. 40 years ago. Hollow, down, no scribe found.
 10" now 15" W.Oak N.53°W., 29.0 ft. Open and find "CS". BT mkd. by Cole in 1921.
 No trace of other orig. BT nor 1" I.P. set by Cole.
 Set Brass cap at cor. mkd: County Surveyors Office

	R8W		T 23 S		R7W
		S 1		S 6	
W.C.		S 12		S 7	
		1965			

Wit. Cor. 20 ft. North

Set 3/4" iron rod for corner in creek bottom.
 New BTs- 11" W.Oak N.64°W., 22.0 ft. mkd. WC T23S R8W S1 CS BT.
 10" W.Oak N.33°E., 21.3 ft. mkd. WC T23S R7W S6 CS BT.
 24" B.Oak S.7°E., 40.5 ft. mkd. WC T23S R7W S7 CS BT
 14" W.Oak S.65°W., 44.6 ft. mkd. WC T23S R8W S12 CS BT.

Fd & used Feb. 1987, L. Roberts - C.S 63/46-5(D); M 103-73
 Found Sept. 1992 by Beckley - M 119-80
 FD. OK by DCSO, 6/13/2002 - C.S. File 66/34-8