

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 133700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 31 only, T22-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1498)

-----  
Set closing ¼ sec. post, from which  
A W.Oak 18" dia., bears N.47°W., 219 lks. dist.  
A W.Oak 10" dia., bears N.8°E., 220 lks. dist.  
School house bears N.12°W., 274 lks. dist.

Volume 2 Page 265 (Surveyor, Date ??)

-----  
Set W.Oak post 4x4x3 from which  
W.Oak 12" bears N.67°54'W., 181 lks.  
W.Oak 13" bears N.48°36'E., 98 lks.  
(Old marks in evidence)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C. Putnam, crew - April/May 1962 - C.S. File 52/125-2

-----  
Found - W.Oak now 28", N.48½°E., 64.7 ft. Cut scar open and found good scribing "SC", approx. 50 years old.  
Oak stump N.68°W., 119.5 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office  
T 22 S R 7 W  
1/4 S 31 only  
T 23 S R 7 W  
1962

New BTs -7" D.Fir N.33°W., 8.7 ft. mkd. ¼ S31 CS BT.  
12" D.Fir N.31°E., 9.3 ft. mkd. ¼ S31 CS BT.  
Corner lies in East and West fence line.

Fd. OK, May 1993, D. Bentz, M 117-6