

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #987, surveyed July/Nov. 1979 - (DCSO records Vol. 42 Page(s) 16585)

(33.18 chains)
Point selected for the witness ¼ sec. cor. of secs.19 and 30.
Set an iron post 28" long, 2½" dia., 26" in the ground, with brass cap mkd: WC
T 23 S R 7 W
S 19
1/4 -----
S 30
1979

from which
A Fir 32" dia., bears N.39¼°E., 10.14 chs. dist. mkd. X BT
An Oak 21" dia., bears S.4p°W., 10.19 chs. dist. mkd. X BT
The witness cor. is located on top of bank on E. side of Umpqua River.
(S.89°18'W.) (39.69 chains)
True point for the ¼ sec. cor. of secs. 19 and 30, is located in the Umpqua River where it is impractical to establish a permanent monument.