TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2496)

Set ¼ sec. post, from which
A Dogwood 7" dia., bears N.55°E., 70 lks. dist.
A W.Oak 4" dia., bears S.40°W., 21 lks. dist.

Douglas County Surveyors Office - Milo Godfrey and crew - C.S. File 52/125-50 - Jan. 1966

Corner searched for, not found.

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #987, surveyed July/Nov. 1979 - (DCSO records Vol. 42 Page(s) 16588-89)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 23 S R 7 W

1/4 S 18 / S 19

1979

from which
A Fir 8" dia., bears N.57½°E., 37 lks. dist. mkd. ¼ S18 BT
A Fir 8" dia., bears S.19½°E., 26½ lks. dist mkd. ¼ S19 BT

Mark Smalley - For: Roseburg Forest Products - Bill Olson - Ralph McManis - Nov 1998 - C.S. File 65/23-5

Found - 1979 BLM BCIP
Fir, 12″, N.57½°E., 24.4 ft.
Fir, 12″ S.19½°E., 17.5 ft.
New BTs- D.Fir 9″, S.47°E., 24.0 ft.
D.Fir 13″ S.66°W., 37.7 ft.