

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias 872080 Description M.C. on left bank Umpqua River

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2497)

-----  
Set meander post, also true ¼ sec. post, from which  
A Myrtle 12" dia., bears S.36°E., 8 lks. dist.  
A Myrtle 12" dia., bears N.9°W., 14 lks. dist.

Douglas County Surveyors Office - Milo Godfrey and crew -  
C.S. File 52/125 - Jan. 1966

-----  
Corner searched for, not found.

Survey by Les Roberts - For: International Paper Company -  
Feb. 15, 1987 - C.S. File 63/46-5(B) and M 103-73

-----  
No evidence of original corner found.  
Set 3/4" x 30" alum. rod with alum. cap stamped with section,  
township, range and PLS #1039. (Buried purple magnetic  
marker under 30" rod.) from which  
15" W.Fir N.47°W., 24.7 ft., scribed, painted red.  
18" W.Fir S.27°E., 17.9 ft., scribed, painted red.