

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2491)

Set ¼ sec. post, from which
A W.Oak 12" dia., bears N.84°E., 91 lks. dist.
A W.Oak 8" dia., bears S.15°W., 58 lks. dist.

Douglas County Surveyors Office - Milo Godfrey and crew -
C.S. File 52/125 - Jan. 1966

Corner searched for, not found.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/20/2002 - C.S. File 66/32-15

Found - 8" now 17" dia., W.Oak, we open small hole & find good scribe mark "B" bears S.15°W. 38.3 ft. (OBT)
Orig. NE BT gone.

Set - A 2 3/8" dia., brass cap on a 1 3/8" by 32" long iron pipe at position determined by OBT protrudes 5" out of ground, mkd: DOUGLAS COUNTY SURVEYORS
T 23 S
¼ S 30 | S 29
R 7 W
2002

17" dia., W.Oak double blazed & scribed "¼ S29 CS
BT" bears S.30°E., 42.8 ft.
10" dia., B.Oak double blazed & scribed "¼ S29 CS
BT" bears N.85°E., 87.5 ft.
21" dia., W.Oak double blazed & scribed "¼ S30 CS
BT" bears N.11°W., 15.0 ft.
Compass decl. 17½°E.

1