TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2496)

Set ¼ sec. post, from which
A W.Oak 18" dia., bears N.6°W., 8 lks. dist.
A W.Oak 16" dia., bears N.32°E., 28 lks. dist.

BLM resurvey by Floyd A. Brooks and Peter A. Peterson, Cadastral Surveyors, under Group #594 - Surveyed Aug/Sept 1965 - (DCSO records Vol. 33 Page(s) 13895-96)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

¼
S 18 S 17
T 23 S R 7 W
1965

from which
A Fir 22" dia., bears N.82½°E., 40½ lks. dist. mkd. ¼ S17 BT.
A Fir 13" dia., bears S.75 3/4°W., 19 lks. dist. mkd. ¼ S18 BT.
Corner falls on spur, slopes W.

Mark Smalley - For: Roseburg Resources - Nov. 1998 - C.S. File 65/20-46

Found - 1965 BLM BCIP.
36" Fir, N.82½°E., 26.7 ft., healed face.
18" Fir, S.75 3/4°W., 12.5 ft., healed face.
New BTs- 13" W.Fir, N.20°W., 22.9 ft., scribed "¼ S BT"
18" D.Fir, N.42°E., 40.0 ft., scribed "¼ S BT"

Fd. & used BLM dependent resurvey by Craig Wanless, Cadastral Surveyor, under Group # 1936, surveyed Sept./Nov. 2000 - (DCSO records Vol. 53 Page(s) 20567-8)