

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2496)

Set post cor. to secs. 17, 18, 7 and 8, from which
A Fir 7" dia., bears S.56°W., 76 lks. dist.
A Fir 7" dia., bears N.50°W., 54 lks. dist.
A Maple 10" dia., bears N.20°E., 17 lks. dist.
A Maple 10" dia., bears S.53°E., 88 lks. dist.

B. B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson;
Loren Weber - Feb. 1940 - C.S. File 16/55

Location identified from snag of original BT, chopped out,
scribe marks legible.

Set 4" x 4" x 48" Fir post for corner from which
Fir 15" dia., bears N.42°E., 13.0 ft.
Fir 12" dia., bears N.75°W., 26.2 ft.
Fir 8" dia., bears S.40½°W., 41.0 ft. (slope)
Fir 14" dia., bears S.15°E., 21.0 ft. (slope)

BLM resurvey by Floyd A. Brooks and Peter A. Peterson,
Cadastral Surveyors, under Group #594 - Surveyed Aug/Sept
1965 - (DCSO records Vol. 33 Page(s) 13896)

The Sec. cor., determined at record bearing and distance from
the remaining original bearing tree:

A Fir snag 14" dia., bears S.56°W., 76 lks. dist., with
scribe marks W T23S 18 BT visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground,
with brass cap mkd:

T 23 S R 7 W
S 7 S 8
S 18 S 17
1965

from which a bearing tree mkd. by Richardson in 1940

A Fir 12" dia., bears S.40½°W., 36 lks. dist., with a
healed double blaze.

and new bearing trees:

A Fir 5" dia., bears N.47°E., 137 lks. dist., mkd. T23S
R7W S8 BT.

A Fir 17" dia., bears S.63½°E., 124 lks. dist., mkd. T23S
R7W S17 BT.

An Alder 7" dia., bears N.12½°W., 118 lks. dist., mkd.
T23S R7W S7 BT.

(Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Douglas Co. Surveyors Office - Gary L. Langlitz; Karen Reed;
Frank Silagy, crew - Nov. 28, 1978 - C.S. File 60/17-29

Found - A 2½" I.P. with 1965 GLO brass cap. Cap was covered
with two feet loose shale, cap located on steep
slide area. This corner continuously buried by
loose shale.

A Fir 5" now a 12" bent Fir, bears N.47°E., 90.4 ft.
with healed over single blaze.

A 17" now 20" Fir bears S.63½°E., 81.8 ft. with
healed over double blaze.

An Alder 7" now 12", bears N.12½°W., 77.9 ft. with
healed over double blaze.

A 12" Fir bears S.40½°W., 23.1 ft. with healed over
double blaze.

Original Fir snag not found.

Left cap in position.

New Bearing Object:

Marked rock bluff with "B O T" which bears N.86°W.,
39.8 ft. Letters and "+" approx. 6" tall.

Corner falls on middle of slide in loose shale.

Fd. OK, Sept. 1992 by Beckley - M 119-80

Fd. & used BLM dependent resurvey by Craig Wanless, Cadastral
Surveyor, under Group # 1936, surveyed Sept./Nov. 2000 -
(DCSO records Vol. 53 Page(s) 20563)