TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 237100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 5 only, T24-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by C. Albert White, Cadastral Surveyor and Donald R. Beck, Surveying Technician, Under Group #515, Surveyed June/Oct. 1963 - (DCSO records Vol. 32 Page(s) 13477)

Point for the ¼ sec. cor. of sec. 5 only, at midpoint longitudinally on the N. bdy. of sec. 5, T24S R7W.
Set an iron post 28" long, 2½" dia., 22" in the ground with brass cap mkd.

¼ S 5
T 24 S R 7 W
1963

from which
A Fir 9" dia., bears S.45°E., 110 lks. dist. mkd. ¼ S5 BT.
No other suitable bearing tree available within limits.

Fd. OK, April 1992 by L. Dolan - M 115-3
Fd. BC & 1 BT, May 2006 by C. Sweeden - M151-20

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 9/26/2006 - C.S. File 67/14-29

Found - 3¼" dia., BLM brass cap on 2½" I.Pipe firmly set projects 8" above ground. (Properly mkd)
9" now 14" dia., x1½ ft. tall rotted D.fir stump. Illegible reverse scribe fd. bears S.45°E., 72.6 ft. (agrees w/rec) 1963 BT.

Set - 21" dia., Pear tree, tagged, not scribed bears S.81¼°W., 139.1 ft.
20" dia., apple tree, tagged, not scribed bears N.46¾°W., 111.1 ft.
17" dia., D.Fir double blazed & scribed "¼ S5 CS BT" bears S.36¼°E., 46.4 ft.
A 3½" dia., brass cap on a 2½" I.Pipe prot. ≈ 1 ft. above ground. (S¼ Sec. 32, T23S R7W) bears N.89°46'E., 176.0 ft (Rec. N.89°46'E., 175.56 ft)

Note - Lies on moderate East facing scope in cleared pasture area approx. 140 ft. East of dirt Rd.
Compass decl. 16½°E.