TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1496-97)

Set standard 1/4 sec. post, from which
A B.Oak 18" dia., bears S.42°E., 184 lks. dist.
No tree S. and W. of line.

Volume 2 Page 264 (Surveyor ?) (Date ?)

Reset stone 5 x 8 x 16", from which
B.Oak 12" bears S.41°43'W., 13 lks.
B.Oak 10" bears S.72°27'E., 24 lks.
Old BTs in evidence.

DCSO MEG May 1, 1962 - fd rock & 2 BTs - C.S. File 52/14-14 - added 3/21/2018

William Beckley for Anderson - Sept. 1992 - M119-80

Found - 5" x 8" Sandstone flush with ground marked "SC"
T iron post with 1" cap marked "Wilford Haines survey point Drain, Or" bears west 0.30 ft. from true corner.
Fd. BTs- 24" B.Oak S.42°W., 8.58 ft. - good scar.
16" B.Oak S.73°E., 16.00 ft. - scar visible.

Found OK by G.Lang, Aug. 1996 - M 125-72
Found OK by M. Heimburger, July 2000 - M135-38
Fd. stone by D. Edwards, 10/2008 - M158-20