

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 272700

PRIMARY CORNER DESCRIPTION C.C. for Secs. 32 and 33 only, T22-7

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1497-98)

Set closing cor. on standard parallel, West 7 chains, 64 lks. from standard cor. of secs. 4 and 5, from which
A B.Oak 18" dia., bears N.55°W., 183 lks. dist.
A Fir 20" dia., bears N.86°E., 94 lks. dist.

Wilford N. Haines - For: Woolley Logging & E.G. Whipple Mill April 1961 - C.S. File 51/191 and M 38-69

Set 1" x 1" x 36" T. Iron.
Scribed - 24" Alder N.31°E., 39.2 ft.

T Iron lies about 10 ft. South of E & W fence line. (Per M.G.)
- Written on previous corner renewal pgs.

DCSO fd ok March 1, 1962 Milo Godfrey C.S. File 52/14-13 (added 3/21/2018):
Fd "T" iron & cap.
Fd. 24" Alder N.31°E., 39.2 ft. bark scribed "CC S33 BT"
No trace of orig. BTs.
Note - This cor. lies approximately dist. called for in orig. field notes west of cor. by Markham (N CC Secs. 4 & 5 T23-7)