

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCS0 records Vol. 6 Page(s) 2462)

Set post cor. to secs. 32, 33, 4 & 5, from which
A Fir 14" dia., bears S.50°W., 20 lks. dist.
A Fir 14" dia., bears N.45°W., 38 lks. dist.
A Chinquapin 8" dia., bears N.16°E., 12 lks. dist.
A Fir 28" dia., bears S.75°E., 54 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey, Clete Putnam, crew - Sept. 1960 - C.S. File 49/49-8

Found - Orig. 14" now 22" R.Fir, N.45°W., 25.1 ft., shows good bark scribing "3 T23S R7W".
Orig. 28" now 38" R.Fir S.75°E., 35.6 ft., shows good bark scribing "S4"
Orig. 8" now 3" spike stump of orig. NE. BT.
Orig. SW. BT not found.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 7 W
S 32 | S 33
T 24 S
1960

New BTs- 10" Cedar bears N.29°E., 35.9 ft. scribed S33 T23S R7W CS BT.
Rescribed now 22" R.Fir N.45°W., 25.1 ft. "S32 T23S R7W CS BT"

BLM Resurvey by C. Albert White, Cadastral Surveyor and Donald R. Beck, Surveying Technician, Under Group #515, Surveyed June/Oct. 1963 - (DCS0 records Vol. 32 Page(s) 13475-76)

The Sec. Cor, perpetuated and recorded by Byron in 1960, monumented with an iron post 1" dia., firmly set, protruding 12" above the ground, with brass cap mkd. in 1960, from which the remains of the original bearing trees:

A Fir 50" dia., bears S.71½°E., 54 lks. dist. mkd. S4 on bark blaze. (Rec. S.75°E.)
A down and rotted Fir 28" dia., bears S.45½°W., 20 lks. dist., no marks remain. (Rec. S.50°W.)
A down Fir 30" dia., bears N.49½°W., 38 lks. dist., mkd. T23S R7W S32 on bark blaze. (Rec. N.45°W.)
and a bearing tree mkd. by Byron:
A Cedar 10" dia., bears N.30°E., 54 lks. dist., mkd. T23S R7W S33 CS BT.

(Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 32 & 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing tree: A Cedar 8" dia., bears N.52½°W., 75 lks. dist. mkd. T23S R7W S32 BT.
Fd. Ok by L. Roberts, Feb. 1980, M84-57
Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Aug. 6, 2014 - C.S. File 67/41-41 ----- Found - 1960 DCS0 2½" dia, brass cap on a 1" I.D. iron pipe set plumb protruding 12" above ground. (MKD) COUNTY SURVEYORS OFFICE T23S R7W <u>S 32 S 33</u> 1960 OBTs - A fir 14" dia., now a large root-hole approximately at the record bearing & distance of orig. SW BT. A fir 14" dia., now a distinct root-hole with a fallen and rotted fir nearby showing the remnants of the 1960 reblaze with clear but illegible fragmentary scribing. The root-hole bears N.45°W., 25.1 ft. (As per record) A fir 28" dia., now 48" dia., 2½ ft. tall rotted fir stump with no remaining blaze or scribe evidence; bears S.75°E., 36.8 ft. (record S.75°E., 35.6 ft. is possible face measurement.) 1960 BT- A 10" cedar now a 25" dia., I.Cedar with a fully healed double blaze; bears N.29°E., 35.9 ft. (as per record) 1963 BLM- A Cedar 8" dia., now a 26" dia., I.Cedar with a fully healed double blaze; bears N.52½°W., 48.7 ft. (rec. N.52½°W., 49.5 is to center of trunk at breast height. New - An 18" dia., D.Fir scribed "T23S R7W S33" "CS BT" on a double blaze; bears N.64¼°E., 23.2 ft. An 11" dia., D.Fir scribed "T23S R7W S32 CS" "BT" on a double blaze; bears N.56½°W., 12.5 ft. Note - Monument is on gentle south slope in open fir, cedar, oak and chinquapin forest. Compass decl. 15½°E.