

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2484-85)

Set ¼ sec. post, from which
A B.Oak 20" dia., bears N.10°W., 234 lks. dist.
A W.Oak 23" dia., bears N.51°E., 132 lks. dist.

J.W. Cole - Wit: C. Springer; Arthur Mode - July 24, 1923 - C.S. File 8/29

Renewed from both original BTs, standing. Tree N.10°W., bearing scribe marks. Other tree not chopped open.
Set 5/8" x 36" iron rod for corner.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow, crew - Sept. 1958 - C.S. File 49/49-6

Found - 5/8" Iron rod at corner.
Orig. 23" now 36" W.Oak N.51°E., 87.1 ft. I open and find good scribing "¼S"
Parts of rotted stump that checks orig. NW. BT.
Set brass cap alongside of iron rod, mkd: County Surveyors Office T23S R7W ¼ S17 S16 1958.
New BTs- 42" R.Fir, S.30°W., 28.6 ft. scribed ¼ S17 CS BT.
24" R.Fir, S.35½°E., 22.0 ft. scribed ¼ S16 CS BT.

BLM resurvey by Floyd A. Brooks and Peter A. Peterson, Cadastral Surveyors, under Group #594 - Surveyed Aug/Sept 1965 - (DCSO records Vol. 33 Page(s) 13891-92)

The ¼ sec. cor., remonumented by the County in 1958, with an iron post 1" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1958, from which an original bearing tree:
A W.Oak 30" dia., bears N.51°E., 132 lks. dist., with scribe marks 4 S visible on opened blaze.
and trees marked by Byron in 1958:
A Fir 30" dia., bears S.35½°E., 34 lks. dist., with fragmentary scribe marks visible on pitched over double blaze.
A Fir 48" dia., bears S.30°W., 44 lks. dist., with fragmentary scribe marks visible on pitched over double blaze.

Fd. OK, Jan. 1994 by D. Bentz - M 119-24

continued next page

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Craig Wanless, Cadastral Surveyor, under Group # 1936, surveyed Sept./Nov. 2000 - (DCSO records Vol. 53 Page(s) 20566)

From the 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1" dia., firmly set, projecting 10" above the ground, with brass cap mkd

COUNTY SURVEYORS OFFICE
T 23 S R 7 W
1/4 S | S
17 | 16
1958

from which the remains of bearing trees mkd. by Byron, Deputy County Surveyor, in 1958, and reported by Brooks and Peterson

A sawed fir stump, 34" dia., bears S.35½°E., 22.4 ft., with a healed blaze.

A sawed fir stump, 48" dia., bears S.30°W., 32.0 ft., no marks visible. (Record, 29.0 ft.)

and new bearing trees

A fir, 11" dia., bears N.13 3/4°E., 55.9 ft. mkd. 1/4 S16 BT

A fir, 12" dia., bears S.73 3/4°W., 14.0 ft. mkd. 1/4 S17 BT

Each new bearing tree has a 2½" by 1/4" magnetic nail (Mag Nail) driven at the base on the right side-center, unless otherwise noted in the corner description.