

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2485)

-
- Set post cor. to secs. 8, 9, 16 and 17, from which
- A W.Oak 8" dia., bears S.8°W., 153 lks. dist.
 - A W.Oak 11" dia., bears N.14°W., 143 lks. dist.
 - A W.Oak 8" dia., bears N.19°E., 163 lks. dist.
 - A W.Oak 10" dia., bears S.58°E., 150 lks. dist.

BLM resurvey by Floyd A. Brooks and Peter A. Peterson, Cadastral Surveyors, under Group #594 - Surveyed Aug/Sept 1965 - (DCSO records Vol. 33 Page(s) 13892-93)

The Sec. Cor., monumented with the base of an Oak post 10 x 8 ins., in cross section, 18" long, firmly set, 18" in the ground. There is no remaining evidence of the original corner. The corner point is substantiated by a signed statement from Mr. Keith Kestersen, a long time property owner and resident of the area, attesting to the true corner position. The statement is hereinafter attached.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 23 S R 7 W
<u> S 8 S 9 </u>
S 17 S 16
1965

from which

- An Oak 36" dia., bears N.60½°E., 688 lks. dist. mkd. T23S R7W S9 BT.
- A Fir 18" dia., bears S.16°E., 21 lks. dist. mkd. T23S R7W S16 BT.
- A Fir 22" dia., bears S.42°W., 49 lks. dist., mkd. T23S R7W S17 BT.
- A Fir 7" dia., bears N.53 3/4°W., 141 lks. dist., mkd. T23S R7W S8 BT.

Deposit remains of the Oak post alongside iron post. The corner falls at the S. edge of a dirt road, 10 lks. wide, bearing NW. and SE.

Fd. OK, Jan. 1995 by D. Bentz - M 119-24

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Craig Wanless, Cadastral Surveyor, under Group # 1936, surveyed Sept./Nov. 2000 - (DCSO records Vol. 53 Page(s) 20559-60)

Beginning at the cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2½" diam., firmly set, projecting 2" above the ground, with brass cap mkd. T 23 S R 7 W

S 8 | S 9
S 17 | S 16
1965

from which the remains of bearing trees mkd. by Brooks and Peterson

A sawed fir stump, 26" dia., bears S.16°E., 13.9 ft., no marks visible.

A sawed fir stump, 24" dia., bears S.42°W., 32.3 ft., no marks visible.

and new reference monuments

An iron rod, 30" long, 5/8" dia., set 30" in the ground for a reference monument, bears N.53°40'21"E., 17.34 ft., with aluminum cap mkd. RM 1.

An iron rod, 30" long, 5/8" dia., set 30" in the ground for a reference monument, bears S.41°47'41"E., 16.47 ft., with aluminum cap mkd. RM 2.

An iron rod, 30" long, 5/8" dia., set 30" in the ground for a reference monument, bears S.69°50'37"W., 23.93 ft., with aluminum cap mkd. RM 3.

An iron rod, 30" long, 5/8" dia., set 30" in the ground for a reference monument, bears N.43°58'27"W., 12.25 ft., with aluminum cap mkd. RM 4.

The corner is located 40 ft. S. of a graveled road, 10 ft. wide, bears N.50°W. and S.50°E.