

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2486)

Set ¼ sec. post, from which
A W.Oak 8" dia., bears S.32°E., 27 lks. dist.
A W.Oak 12" dia., bears N.9°E., 67 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 1965 - C.S. File 52/125-14

Found - Orig. 8" now 20" W.Oak N.9°E., 44.2 ft. We open and find "¼S", reverse scribing.
No trace of SE. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 7 W
¼ $\frac{S}{S} \frac{4}{9}$
1965

New BTs- 18" W.Oak N.1°E., 143.6 ft. mkd. ¼ S4 CS BT.
18" W.Oak S.71°E., 215.5 ft. mkd. ¼ S9 CS BT.
Corner lies approx. 260 ft. West of top of river bluff in open field.

Corey M Woodruff - For: Elkton Reserve, LLC & the USA - 1/2012 - M163-30A-C

Found - Douglas Co. Surveyor IP w/BC per CS 52/125
BT FD - 28" W.Oak brs. S.71°E., 214.3'
BT mkd- 15" D.Fir brs. N.39°E., 300.2'