

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1496)

Set standard 1/4 sec. post, from which
A W.Oak 20" dia., bears S.87°E., 920 lks. dist.
A W.Oak 15" dia., bears S.54°W., 324 lks. dist.

Wilford N. Haines - For: Woolley and Whipple - April 1961 - C.S. File 51/191 and M 38-69 (Map filed in 1969)

Set 1" x 1" x 36" T Iron.
Scribed -12" D.Fir S.60°W., 21.5 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - June 11, 1962 - C.S. File 52/14-8

Found - Haines "T" Iron and cap.
12" D.Fir S.57°W., 21.1 ft., blazed and scribed, not legible, completely pitched over, Haines' metal disc on tree.
An old Oak stump, uprooted, showing an upper and lower scar, both of which are completely rotted out inside, bears S.87°E., 641.8 ft. Govt. notes call for a 20" W.Oak S.87°E., 607.2 ft.
No trace of old SW BT found.

Corey M Woodruff - For: Elkton Reserve, LLC & the USA - 1/2012 - M163-30A-C

Found - T-iron
BT FD - 31" D.Fir brs. S.58°W., 20.8' (healed face)
BTs mkd- 23" D.Fir brs. N.52°W., 24.2'
27" D.Fir brs. N.70°E., 18.7'