

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 376360

PRIMARY CORNER DESCRIPTION SE Cor. Govt. lot #1, Sec. 21

Alias <u>870550</u>	Description <u>Special M.C. left bank Umpqua Riv.</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCSO records Vol. 31 Page(s) 13168-69)

-----  
Point for the special meander cor. of sec. 21 at intersection with the adjusted meander line on the left bank of the Umpqua River.

Set an iron post 28" long, 2½" dia., 12" in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked:

N	S	N
	21	SMC
		1963\

from which

- A Fir 11" dia., bears N.47 3/4°W., 7 lks. dist. mkd. SMC S21 BT.
- A Fir 8" dia., bears S.20°E., 44½ lks. dist. mkd. SMC S21 BT.

From this point, the meander cor. of secs. 21 and 22, on the left bank of the Umpqua River, bears S.15°05'E., 18.67 chs. dist.

Bruce Shaner, surveyed for Edwin Kausche; May-June 1996 - M 124-20 & corner report in CS 65/2-13B

-----  
Found - 1963 U.S.B.L.M. Brass Cap w/iron pipe  
18" D.Fir BT, face overgrown, bears N.47 3/4°W., 6.7' (rec. 4.6')  
18" D.Fir BT, face overgrown, recently sawed off, bears S.20°E., 29.4 ft.

New Accessories -

- 12" Myrtle BT, I bark scribed "SMC BT" bears S.2½°E., 11.5 ft.
  - 6 foot steel fence post bears West, 1.0 ft.
- Corner lies on north side of newly logged area.