

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 376400

PRIMARY CORNER DESCRIPTION M.C. on South bdy. Sec. 16

Alias <u>870560</u>	Description <u>M.C. on Left bank Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2484)

Left bank of Umpqua River, where set post cor. to fractional secs. 21 and 16, from which

A Myrtle 4" dia., bears N.50°E., 25 lks. dist.

An Ash 15" dia., bears S.40°E., 18 lks. dist.

This cor. is West of the cor. to fractional secs. 15 and 22 on the right bank of river.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #330, Surveyed Aug. 1957 (DCSO records Vol. 28 Page(s) 12095)

Foot of slope, bears N.30°W. and S.30°E., along edge of bottom. Point for the meander cor. of secs. 16 and 21, on the left bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30" long, 2½" dia., 24" in the ground, with brass cap mkd: T23S

S 16

S 21
R7W
1957

from which

A Myrtle 12" dia., bears N.7°W., 35 lks. dist. mkd. T23S
R7W S16 MC BT.

A Fir 48" dia., bears S.83°W., 64 lks. dist., mkd. T23S
R7W S21 MC BT.

Fd. OK, Jan. 1994 by D. Bentz - M 119-24