

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2471)

-----  
Set 1/4 sec. post, from which  
A W.Oak 18" dia., bears S.9°E., 312 lks. dist.  
A W.Oak 10" dia., bears S.27°W., 308 lks. dist.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #456, Surveyed Aug 1961/Jan. 1962 (DCSO records Vol. 31 Page(s) 13080-81)

-----  
The 1/4 corner, determined at record bearing and distance from the only remaining original bearing tree:

A W.Oak 35" dia., bears S.9°E., 312 lks. dist., with rotted blaze showing axe marks but no scribe marks.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 23 S R 7 W  
1/4  
S 33 S 34  
1961

from which  
A Fir 8" dia., bears N.5 1/2°E., 136 lks. dist. mkd. 1/4 S34 BT.  
A Fir 15" dia., bears N.12 3/4°W., 121 lks. dist. mkd. 1/4 S33 BT.

Mark Smalley - For: Riverbend Resources - June 1998 - M 129-30-

-----  
Found - 40" W.Oak, S.5 1/2°E., 207.2 ft., (S.9°E., 205.9 ft) Orig.  
14" Fir, N.7 1/4°E., 90.5 ft., (N.5 1/2°E., 89.8 ft) Rescribed "1/4 S BT"  
Set - 3/4" x 36" aluminum rod with aluminum cap and magnet locator flush with ground marked "RLS 2354 1998"  
36" W.Oak, S.51°W., 317.7 ft., "1/4 S BT".