

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2472)

-----  
Set post cor. to secs. 33, 34, 27 and 28, from which  
A Laurel 18" dia., bears S.32°W., 16 lks. dist.  
A Fir 6" dia., bears N.40°W., 14 lks. dist.  
A Fir 10" dia., bears N.10°E., 10 lks. dist.  
A Laurel 14" dia., bears S.55°E., 33 lks. dist.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #456, Surveyed Aug 1961/Jan. 1962 (DCSO records Vol. 31 Page(s) 13080)

-----  
Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd:

T 23 S R 7 W  
S 28 | S 27  
S 33 | S 34  
1961

from which

- A Madrone 11" dia., bears N.18°E., 64 lks. dist. mkd. T23S R7W S27 BT.
- A Maple 18" dia., bears S.53 3/4°E., 168 lks. dist. mkd. T23S R7W S34 BT.
- A W.Fir 8" dia., bears S.78½°W., 224 lks. dist. mkd. T23S R7W S33 BT.
- A W.Fir 15" dia., bears N.84½°W., 148 lks. dist. mkd. T23S R7WS28 BT.

Fd. OK, March 1983 by D. Bentz - M 90-38 A&B

Fd. and tied in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1102, surveyed July/Aug. 1982 - (DCSO records Vol. 46 Page(s) 17601)

Fd ok by Mark Smalley - 6/1998 - M 129-30  
Fd. Ok by Mark Smalley ½005 - M147-73