

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2473)

Set post cor. to secs. 27, 28, 21 and 22, from which
A B.Oak 30" dia., bears S.47°W., 38 lks. dist.
A W.Oak 24" dia., bears N.32°W., 130 lks. dist.
A B.Oak 30" dia., bears N.65°E., 77 lks. dist.
A B.Oak 40" dia., bears S.12°E., 56 lks. dist.

W.H. Woods, Deputy Surveyor - Wit: W.S. Crear; Chas. Smith; J. Mode; S.F. Anderson - Nov. 9-10, 1925 - C.S. File 3/26 and Vol. 3 Pag. 233

Set from old BTs:
Red Fir 12", N.80°30'W., 79 lks. "BT S21 CS"
Oak 36" dia., bears S.71°W., 149 lks. "BT S28 CS"
Oak 36" dia. S.75°E., 21 lks. "BT S27 CS"
Oak 30" dia. N.65°E., 77 lks. (Old BT)

Fd. July 1955 - M 9-31

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #456, Surveyed Aug 1961/Jan. 1962 (DCSO records Vol. 31 Page(s) 13082-83)

The Sec. cor., monumented with the original Oak post, 5 x 6 ins., in cross section, 24" long, firmly set, 8" in the ground, with fragmentary scribe marks visible, from which the remaining original bearing tree:

A W.Oak 50" dia., bears N.65°E., 77 lks. dist., with burned blaze.
and trees mkd. by the County in 1925:
A stump hole, bears S.75°E., 21 lks. dist.
A W.Oak 50" dia., bears S.71°W., 149 lks. dist., with a healed double blaze.
A Fir 25" dia., bears N.80½°W., 79 lks. dist., with a healed double blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 23 S R 7 W
S 21 S 22
S 28 S 27
1961

from which
A Fir 11" dia., bears N.5 3/4°E., 18½ lks. dist. mkd. T23S R7W S22 BT.
(Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

A Fir 15" dia., bears S.86°E., 67 lks. dist. mkd. T23S R7W S27 BT. Deposit the original post alongside the iron post.	
Fd. and used in BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCSO records Vol. 31 Page(s) 13161)	
FD. OK, by B. Shaner - April 1997 - M 126-77 & C.S. 65/13-7B	
Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/29/2002 - C.S. File 66/34-24 -----	
Found -	1961 BLM brass cap/iron pipe protrudes 1" out of ground. 12" now 31" dia. 3 ft. high D.Fir stump with a fully healed blaze bears N.80½°W., 52.1 ft. (1925) 36" now 61" dia., B.Oak with a healed blaze S.71°W., 98.3 ft. (1925) 11" now 27" dia., 2½ ft. high D.Fir stump with a fully healed lower blaze, bears N.5¾°E., 12.2 ft. (1961) 15" now 30" dia., 2 ft. high D.Fir stump, bears S.86°E., 44.2 ft. (1961)
New -	16" dia., W.Oak double blazed & scribed "T23S R7W S21 CS BT" bears N.69°W., 17.3 ft. 25" dia., W.Oak double blazed & scribed "T23S R7W S28 CS BT" bears S.51°W., 26.4 ft. 5" dia., D.Fir double blazed & scribed "X CS BT" bears S.33°E., 23.5 ft. Compass decl. 17¼°E.