

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 21 and 22

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2474)

-----  
Set ¼ sec. post, from which  
A Laurel 10" dia., bears S.10°W., 16 lks. dist.  
A Fir 10" dia., bears N.12°E., 9 lks. dist.

W.S. Woods, Deputy Co. Surveyor - Wit: W.S. Crear; Chas. Smith; J. Mode; S.F. Anderson - Nov. 1925 - C.S. File 3/26 and Vol. 3 Page 233

-----  
Stone 4" x 4" x 20" marked ¼ Sec. 21, 22, from which  
Red Fir, N.24°30'E., 8 lks. "¼ S22 CS"  
Laurel 15", N.43°W., 30 lks. "¼ S21 CS".

Wilford N. Haines, #239 - For: E.G. Whipple Mill and Mt. Baldy Lumber Co. - June 1959 to June 1961 - M 22-4

-----  
Found rock mkd. C.S.  
Set 1" x 1" x 36" T Iron.  
Rescribed: 18" Madrone N.45°W., 30 lks. This tree is mentioned in GLO notes as S.4 /34°W., 274 lks. from meander corner S.21 and S22.  
Orig. 10" Fir, N.12°E., 9 lks. is now a 36" stump.  
It had also been scribed when about 20".

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCSO records Vol. 31 Page(s) 13162)

-----  
The ¼ sec. cor., perpetuated in 1925 by Woods, with a sandstone 16 x 4 x 2 ins., firmly set, 10" in the ground, marked with a cross (+) on top and ¼ on the E. face. In 1959, Haines set a 36 x 1 x 1 in. T Iron, 30" in the ground, alongside the sandstone, from which the remaining original bearing tree:

A sawed Fir stump 36" dia., bears N.12°E., 9 lks. dist., with fragmentary scribe marks visible on opened blaze. (This tree was re-marked in 1925 by Woods.)  
and a tree marked by Woods:  
A Madrone 22" dia., bears N.45°W., 30 lks. dist., with decayed blaze. (This tree was re-marked ¼ S BT on the bark by Haines in 1959.)

At the corner point  
(Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground,  
with brass cap mkd:  $\frac{1}{4}$

S 21 S 22  
T 23 S R 7 W  
1963

from which new bearing trees

A Fir 6" dia., bears N.14°E., 59 lks. dist. mkd.  $\frac{1}{4}$  S22 BT.

A Fir 6" dia., bears N.23°W., 59 lks. dist. mkd.  $\frac{1}{4}$  S21 BT.

Deposit the sandstone and the T Iron alongside the iron post.

Bruce Shaner, surveyed for Edwin Kausche; May-June 1996 - M  
124-20 & corner report in CS 65/2-13C

-----  
Found - 1963 U.S.B.L.M. Brass Cap w/iron pipe  
36" D.Fir BT stump bears N.12°E, 5.9 ft.  
24" Madrone BT, face overgrown, bears N.45°W., 19.8  
ft.  
8" D.Fir BT, face overgrown, bears N.14°E., 38.9 ft.  
6" D.Fir BT, now windfall, bears N.23°W., 38.9 ft.

Sandstone & T-iron are alongside corner.

New Accessory -

6 foot steel fence post bears West, 1.0 ft.

Corner on timber edge near top of hill, 161 feet south of  
meander corner.