

PRIMARY CORNER DESCRIPTION M.C. on East bdy. Sec. 21

Alias <u>870540</u>	Description <u>M.C. on left bank Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2474)

-----  
Left bank of Umpqua River which is 300 ft. high, where set post for cor. to fractional secs. 21 and 22, from which  
A Laurel 5" dia., bears S.50°E., 17 lks. dist.  
A Fir 20" dia., bears S.89°W., 39 lks. dist.

W.H. Woods, Deputy Surveyor - Wit: W.S. Crear; Chas. Smith; J. Mode; S.F. Anderson - Nov. 1925 - C.S. File 3/26 and Vol. 3 Page 233

-----  
Left bank of river. Stone 4" x 8" x 24" marked F. S. 21 22, from which  
Red Fir 60", S.07°15"E., 52 lks. BT F.S. 22 C.S.  
Red Fir 18", S.89°W., 39 lks. (Old tree)

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #330, Surveyed Aug. 1957 (DCSO records Vol. 28 Page(s) 12096-97)

-----  
The meander cor. of secs. 21 and 22, determined at the record bearing and distance from the remaining original bearing tree:

A sawed Fir stump 20" dia., bears S.89°W., 39 lks. dist., marked FS21 on partly healed upper blaze; the BT blaze is healed.

At the corner point  
Set an iron post, 30" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

M C  
S 21 S 22  
T 23 S R 7 W  
1957

from which new bearing trees:

A Fir 8" dia., bears S.27½°E., 58½ lks. dist. mkd. T23S R7W S22 MC BT.

A Fir 6" dia., bears N.63¼°W., 45½ lks. disst. mkd. T23S R7W S21 MC BT.

A Madrona 18" dia., bears S.4 3/4°W., 274 lks. dist. mkd. with axe marks visible around opened and decayed face, which Frank Kausch states had visible scribe marks ¼ S until very recently, evidently the original SW. bearing tree for the ¼ sec. cor. of secs. 21 and 22. (See page 12097 for Frank Kausch affidavit)

The meander cor. is located at the top of a bluff, 540 ft. higher than the Umpqua River, edge of bluff bears N.30°W. and S.30°E.  
(Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 400342

PRIMARY CORNER DESCRIPTION M.C. on East bdy. of Sec. 21

Alias 870540 Description M.C. on left bank of Umpqua River  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Fd. and used in BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCSO records Vol. 31 Page(s) 13162)

Bruce Shaner, surveyed for Edwin Kausche; May 1996 - M 124-20 and corner report filed in CS 65/2-13A

-----  
Found - 1957 U.S.B.L.M. Brass cap w/iron pipe  
18" D.Fir BT, face overgrown, bears S.27½°E., 38.6 ft.  
12" D.Fir BT, face overgrown, bears N.63¼°W., 30.0 ft.  
24" Madrone BT, face overgrown, bears S.4 3/4°W., 180.8 ft.

New Accessories -  
6 foot steel fence post bears West, 2.0 ft.  
6 foot steel fence post bears N.3°W., 1.2 ft.  
Corner sets on the top edge of cliff.