

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2476)

-----  
Set post cor. to secs. 9, 10, 15 and 16, from which  
A Laurel 3" dia., bears S.30°W., 56 lks. dist.  
A Fir 36" dia., bears N.60°E., 9 lks. dist.  
A Fir 36" dia., bears N.20°W., 17 lks. dist.  
A Laurel 3" dia., bears S.10°E., 88 lks. dist.

-----  
Wilford N. Haines, #239 - For: E.G. Whipple Mill and Mt. Baldy Lumber Co. - June 1959 to June 1961 - M 22-4

-----  
Drove 1½" x 4 ft. Iron pipe, 40" in ground, scribed:  
56" Fir N.23°E., 66.5 ft.  
8" Fir N.85°E., 48.5 ft.  
14" Oak with location tags and old cruiser marks, bears N.65°E., about 10 ft.  
I found stub of Fir mkd. S9 BT scribed on NE. side, no other evidence.  
Set corner S.20°E., 17 lks.