

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 420300

PRIMARY CORNER DESCRIPTION West 1/16 cor. between secs. 22 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson;
W.E. Holcomb; Kausche - Sept. 1929 - C.S. File 37/6 and Vol
3 Pg. 299

Drove 1½" x 48" Pipe, 44" in ground midway between ¼ cor. 22
& 27 and Sec. cor. 21, 22, 27 and 28. Post along side
scribed S 1/16 S CS S27 S22, from which
28" Fir bears N.2°E., 23 lks. scribed and blazed W 1/16 S
22 CS BT.
24" Fir bears S.82½°W., 12 lks., blazed and scribed W 1/16
S27 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 7/29/2002 - C.S. File 66/34-23

Found - 1¼" I.D. iron pipe protrudes 1" out of ground at
angle point in fence line fence runs N.50°W., +
East from corner (1929)
24" now 26" dia., 2½ ft. high rotted D.Fir stump
bark scribing found several lines & an "S" bears
S.82½°W., 8.9 ft. to center (rec. S.82½°W., 7.9
ft. dist. would be to bark scribing) 1979
28" now 40" 2 ft. high D.Fir stump no marks fd bears
N.16°E., 15.2 ft. (rec. N.2°E., 15.2 ft.) 1929
New - 14" dia., D.Fir double blazed & scribed "W 1/16 S22
CS BT" bears N.32½°W., 20.7 ft.
15" dia., D.Fir double blazed & scribed "W1/16 S27
CS BT" bears S.1°W., 5.0 ft.
Compass Decl. 17¼°E.