

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2479)

Set ¼ sec. post, from which
 A W.Oak 20" dia., bears S.75°E., 328 lks. dist.
 A W.Oak 12" dia., bears N.86°E., 570 lks. dist.

John M. Phillips - Snellstrom Lumber Co. - March 29, 1958 - C.S. File 42/350

¼ corner of 3 and 10 set from one original BT.

Wilford N. Haines, #239 - For: E.G. Whipple Mill - 1960 - M 18-33

Found brass cap set by John Phillips, 2 BTs., orig. Oak and new Fir.

Douglas Co. Surveyors Office - F.L. Ingram and crew - Jan. 1973 - C.S. File 56/24

CORNER REPORT ONLY
Found - Brass cap mkd. "LS 307 T23S R7W 3/10
 16" Fir, now snag, N.36°W., 266.0 ft. scribed S3-307
 (done with knife)
 Orig. 20" W.Oak S.75°W., 216.5 ft., shows scar.
 No trace of NE. BT.