

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 34 & 35 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2463-64)

Set post cor. to secs. 34, 35, 2 and 3, from which
A B.Oak 10" dia., bears S.17°E., 9 lks. dist.
A B.Oak 8" dia., bears S.5°E., 10 lks. dist.
A W.Oak 9" dia., bears N.17°W., 16 lks. dist.
A W.Oak 5" dia., bears N.28°E., 35 lks. dist.

Fd. and used in GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2516)

Douglas Co. Surveyors Office - Frank Cain - Dec. 1929 - Field Book 33 Page 22

Sandstone 6" x 13" x 21" marked with X on top, from which
B.Oak 20" marked C.S. Sec. 35, N.49°E., 176 lks.
Fir 30" marked C.S. Sec. 35, N.83 3/4°E., 130 lks.
No other trees.

BLM resurvey by Floyd Brooks, Cadastral Surveyors - under Group # 456 - surveyed Aug. 1961/Jan. 1962 - (DCSO records Vol. 31 Page(s) 13071-72)

The Sec. Cor., perpetuated by the Deputy County Surveyor in 1929, from original corner evidence which is no longer in existence, with a sandstone 21 x 13 x 6 ins., firmly set, 12" in the ground, mkd. with a cross (+) on top, from which locally established bearing trees:

A fallen B.Oak 20" dia., bears N.49°E., 176 lks. dist., with fragmentary scribe marks visible on decayed face of blaze.

A sawed Fir stump 40" dia., bears N.83 3/4°E., 130 lks. dist., with scribe marks S3 T23S R7W BT visible on opened double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T 23 S R 7 W
S 34 S 35
S 2
T 24 S
1961

from which new bearing trees:

A B.Oak 15" dia., bears N.19 3/4°E., 149 lks. dist. mkd. T23S R7W S35 BT.

(Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION So. Sec. Cor. for 34 & 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A forked W.Fir 70" dia., bears N.5½°W., 377 lks. dist.,
mkd. T23S R7W S34 BT.
Deposit the County Surveyors corner stone alongside the iron
post.

Fd. OK, July 1980 by Charles Giles - M 79-52

Fd. OK, Oct. 1993 by R. Dolan - M 118-17

Mark Smalley - For: Riverbend Resources - June 1998 - M 129-30-

Found - 1961 BLM brass cap on iron pipe.
Stone with X West 3 ft.
20" B.Oak, N.49°E., 116.2 ft., down.
40" Fir stump, N.83 3/4°E., 85.8 ft., scribe
visible.
15" B.Oak, N.19 3/4°E., 98.3 ft., healed.
83" Triple D.Fir, N.5½°W., 248.8 ft., healed.
(Forked W.Fir)
Scribed- 8" Fir, S.45°E., 63.8 ft., "SC BT"
42" W.Oak, S.18°E., 61.0 ft., "SC BT"

Found OK by M. Smalley, Sept. 2002 - M141-7