

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2465)

Set post cor. to secs. 34, 35, 26 and 27, from which
A Fir 14" dia., bears S.70°W., 30 lks. dist.
A Fir 8" dia., bears N.88°W., 13 lks. dist.
A Cedar 9" dia., bears N.4°E., 27 lks. dist.
A Yew 5" dia., bears S.88°E., 53 lks. dist.
(Mount Lama Scoocum bears S.75°E.)

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2522)

Witness trees standing. Set new post, from same viz:
A Fir 4" dia., bears S.70°W., 30 lks. dist.
A Fir 8" dia., bears N.88°W., 13 lks. dist.
A Cedar 9" dia., bears N.4°E., 27 lks. dit.
A Yew 5" dia., bears S.88°E., 53 lks. dist.

Claude Kerr - March 1949 - C.S. File 40/190

Found the Cedar BT, scribe visible.
Set 3" x 4 ft. Yew post for corner.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #456, Surveyed Aug 1961/Jan. 1962 (DCSO records Vol. 31 Page(s) 13074)

The Sec. Cor., determined at record bearing and distance from the remaining original bearing tree:

A Cedar snag 27" dia., bears N.4°E., 27 lks. dist. with scribe marks SS visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, to solid rock, with brass cap mkd:

T 23 S R 7 W
S 27 | S 26
S 34 | S 35
1961

from which

A Fir 17" dia., bears S.43 3/4°E., 10 lks. dist. mkd. T23S R7W S35 BT.

A Fir 14" dia., bears S.44°W., 154 lks. dist. mkd. T23S R7W S34 BT.

A Fir 17" dia., bears N.9¼°W., 42 lks. dist. mkd. T23S R7W S27 BT.

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Mark Smalley - For: Riverbend Resources - 6/1998 - M 129-30

Found - 1961 BLM brass cap on iron pipe.
29" Fir, S.43 3/4°E., 6.6 ft., healed.
14" Fir, S.44°W., 101.6 ft., down.
32" Fir, N.9¼°W., 27.7 ft., healed.
27" Cedar snag, N.4°E., 17.8 ft., down - Orig.
Scribed- 11" Fir, S.19°E., 32.2 ft., "S 35 BT"
9" Fir, S.58°W., 42.4 ft., "S 34 BT"

FD. 3 BTs & set 6' steel post 2' North by David Edwards -
4/2006 - M 150-27