

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2466)

Set a post for cor. to secs. 22, 23, 26 and 27, from which
A W.Oak 10" dia., bears N.83°W., 235 lks.
A W.Oak 10" dia., bears S.5°W., 125 lks.
A W.Oak 12" dia., bears N.77°E., 165 lks.
A W.Oak 8" dia., bears S.26°E., 198 lks.

Fd. and used in GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2523-24)

Wilford N. Haines, #239 - For: E. G. Whipple Mill and Mt. Baldy Lumber Co. - June 1959 to June 1961 - M 22-4

Used fence for latitude, record distance East for departure.
Set 1" x 1" x 36" T Iron, from which scribed
24" Fir N.85°E., 38.2 ft.
36" I.Cedar S.17°W., 71.2 ft.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #456, Surveyed Aug 1961/Jan. 1962 (DCSO records Vol. 31 Page(s) 13076)

The sec. cor., recorded and reestablished by Haines in 1961, using an old E. and W. fence line for latitudinal control and the record distance from the West for longitudinal control. Since there is no remaining evidence of the original corner, this is accepted as the best available evidence of the position of the original corner. The corner is monumented with a 1" T Iron 36" long, firmly set, 26" in the ground, with an alum. cap mkd. Wilford N. Haines 239 Survey Point, Drain Ore., from which

A Fir 24" dia., bears N.86 3/4°E., 60½ lks. dist. with scribe marks T23S R7W S23 BT visible on unhealed blaze.
An Incense Cedar 26" dia., bears S.16¼°W., 108 lks. dist., with scribe marks T23S R7W S27 BT visible on unhealed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T 23 S R 7 W
S 22 | S 23
S 27 | S 26
1961

(Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>from which A W.Oak 10" dia., bears N.81½°W., 83 lks. dist. mkd. T23S R7W S22 BT. No suitable bearing tree available in the SE. quadrant. Deposit the Haines monument alongside the corner post.</p>
<p>FD. ok by Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/31/2002 - C.S. File 66/34-28</p>
<p>Fd. ok by D Edwards, 4/2006 - M150-27</p>