

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2467)

-----  
Set a ¼ sec. and meander post, from which  
A Myrtle 6" dia., bears S.5°W., 9 lks. dist.  
A Myrtle 5" dia., bears N.5°E., 9 lks. dist.

-----  
Wilford N. Haines, #239 - For: E.G. Whipple Mill and Mt. Baldy Lumber Co. - June 1959 to June 1961 - M 22-4

-----  
Set 1" x 1" x 36" T. iron.  
(Note: Haines established 1/4 cor. for 22 and one for S. 23. G.I.S. computations and BLM resurvey shows common corner) V. Laugen, Jan. 1997)

-----  
BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #456, Surveyed Aug 1961/Jan. 1962 (DCSO records Vol. 31 Page(s) 13077-78)

-----  
Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the orig. corner.

Set an iron post 28" long, 2½" dia., 26" in the ground, with brass cap mkd:

¼  
S 22 S 23  
T 23 S R 7 W  
1961

from which

A Myrtle 8" dia., bears S.32°E., 44½ lks. dist. mkd. ¼ S23  
BT.

A Myrtle 8" dia., bears N.4°W., 66 lks. dist. mkd. ¼ S22  
BT.

From this point, a cor. established by Haines bears N.75°W., 0.03 chs. dist., monumented with a 1" T Iron, firmly set, projecting 3" above ground, with an alum. cap mkd. Wilford N. Haines 239 Survey Point Drain, Ore.