

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 500436

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 14 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2468)

Set ¼ sec. post, from which
 A Laurel 12" dia., bears S.60°W., 25 lks. dist.
 A Laurel 8" dia., bears N.80°E., 19 lks. dist.
This post is at the summit of mountain, which overlooks the river, course E. and W.

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2526)

Set Fir post, from which
 A Fir 12" dia., bears N.80°E., 16 lks. dist.
 A Fir 12" dia., bears S.55°W., 10 lks. dist.

*(Note: the above GLO notes were for a "common" corner.)
Haines notes that follow, established 1/4 corner for sec. 14 only) V. Laugen, Jan. 1997*

Wilford N. Haines, #239 - For: E.G. Whipple Mill - Filed Jan. 15, 1959 - M 13-64

Set Lot Marker 1' x 1" x 36" Iron with brass cap inscribed: "Survey Point - Wilford N. Haines #239"., from which
 6" Fir S.29°W., 20.3 ft.
 16" Fir N.20°E., 21.6 ft.

Dan Baker - For: Rocking "C" Ranch - 12/2014 - M169-14

Found - 1"x1" "T" iron and cap per M13-64
 32" Fir, N.20°E., 21.6' to center, M13-64
 30" Fir, S.29°W., 20.2' to center, M13-64