

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 15 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2468)

Set ¼ sec. post, from which
A W.Oak 14" dia., bears N.60°W., 18 lks. dist.
A W.Oak 12" dia., bears S.35°E., 40 lks. dist.

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2526)

Set Fir post, from which
A Fir 12" dia., bears N.80°E., 16 lks. dist.
A Fir 12" dia., bears S.55°W., 10 lks. dist.

(Note: the above GLO notes are for a "common" corner - Haines notes that follow established a 1/4 cor. for sec. 15 only) V. Laugen - Jan. 1997

Wilford N. Haines, #239 - For: Whipple - June 1959 - M 13-64

Set 1" Pipe with brass cap.

Dan Baker - For: Rocking "C" Ranch - 12/2014 - M169-13

Found - 1" iron pipe with 3" brass cap "LS 307" set in 1957
(no record) marked:

LS 307
T23S
 |
¼ S S
 15|
 R7W
 1957

Marked - 20" Fir, S.81°W., 17.0' to center, scribed "¼S15BT"
9" Madrone, N.3°W., 9' to center, scribed "¼S15BT"