

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2469)

Set post cor. to secs. 10, 11, 14 and 15, from which
A Fir 16" dia., bears S.25°W., 24 lks. dist.
A Fir 30" dia., bears N.12°W., 8 lks. dist.
A Myrtle 10" dia., bears N.75°E., 39 lks. dist.
A Myrtle 6" dia., bears S.68°E., 42 lks. dist.

Wilford N. Haines - For: E.G. Whipple Mill - Filed Jan. 15, 1959 - M 13-64

Set proportion distance lat., record dist. East.
Set lot marker 1" x 1" x 36" Iron with brass cap inscribed "Survey Point - Wilford N. Haines #239", from which scribed:
12" Fir N.68°30'W., 16.0 ft.
10" Fir S.57°W., 16.2 ft.
30" Fir S.59°45'E., 223.6 ft.

(Note: Haines survey suggests that the above corner is for secs. 10 and 15 only. F.L. Ingram's GIS computations show a "common" corner for 10, 11, 14 and 15.) V.Laugen, Jan. 1997

Dan Baker - For: Rocking "C" Ranch - 12/2014 - M169-13

Position of sec. cor. 10 & 15 only
Found - 48" Fir stump, S.59°45'E., 223.60' per M13-64
Nothing set - corner falls in plowed field