

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 2 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2529)

Set a Fir post for the ¼ sec. cor. to sec. 2, from which
A Fir 12" dia., bears N.11°E., 13 lks. dist.
A Fir 10" dia., bears N.72°W., 124 lks. dist.

Wilford N. Haines, #239 - For: E.G. Whipple - Jan. 15, 1959 - M 11-25

Found 1" Iron pipe, from which
Fir stub, N.11°E., 13 lks.
Fir S.72°E., 124 lks.
16" Fir N.25°30'E., 31.0 ft. scribed about 2 years ago.

Wilford N. Haines, #239 - For: E.G. Whipple Mill - File April 28, 1960 - M 18-33

Set 1" x 1" x 36" T Iron.
Found - 1" Iron pipe, N.86°W., 64.9 ft.
36" Fir N.11°E., 13 lks. scribed in 1881
18" Fir S.25°E., 31.7 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew June 22, 1966 - C.S. File 51/125-51

Found - Haines T Iron as recorded.
Orig. 12" now 46" Fir N.11°E., 8.6 ft., now shattered stump, previously opened and shows "¼S". Approx. 75 years old.
Other orig. BT and Haines' BT, now gone.
Do not find 1" I.P. called for by Haines.
Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 7 W
¼ | S 2
1966
New BTs- 7" W.Fir S.20°E., 7.2 ft. mkd. ¼ S2 CS BT.
7" D.Fir N.21°E., 25.2 ft. mkd. ¼ S2 CS BT.
Corner lies on NE. slope of hill approx. 300 ft. South of ravine, course S.W.

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - S.J. Flauser; R.W. Smith, crew - Wit: Rhonda Amer - Feb. 7, 1986 - C.S. File 62/31-3

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 2 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found - Iron pipe with 1966 DCSO brass cap properly mkd. and firmly set.
1" dia. Iron pipe referred to by Haines as N.86°W., 64.9 ft.
Orig. BT, a 12" Fir, now a shattered Fir stump 36" dia. with fragmentary scribing visible on blaze, bears N.11°E., 8.6 ft.
Possible orig. BT, recorded as 18" Fir S.25°E., 31.7 ft., is dead and down, out of position and partially decayed. We find scribing possible "S" and "B" along with old axe notch in old blaze. (see photos in C.S. File)
Rec. Orig. BT, 10" Fir N., 72°W., 124 lks., not found
7" W.Fir S.20°E., 7.2 ft. is dead and down.
7" D.Fir now an 8" dia. snag bears N.21°E., 25.2 ft.
New BTs- 8" dia. D.Fir double blazed and scribed "¼ S2 CS BT", bears S.62½°E., 34.6 ft.
6" dia. D.Fir double blazed and scribed "¼ S2 CS BT" bears S.35°E., 48.3 ft.
13" dia. D.Fir double blazed and scribed "¼ S2 CS BT", bears N.56°E., 47.4 ft.

Fd. Ok by Carl Sweeden, 2/2006 - M154-12