

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 3 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2471)

Set ¼ sec. post, from which
A Fir 22" dia., bears S.3°W., 120 lks. dist.
A Cedar 36" dia., bears S.38°E., 158 lks. dist.

Wilford N. Haines, #239 - For: E.G. Whipple Mill - Filed April 28, 1960 - M 18-33

Set 1" x 1" x 36" T. Iron, from which
Found 1" Iron pipe and 2 BTs, scribed in 1881.

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - S.J. Flause, R.W. Smith, crew - Wit: Rhonda Amer - Feb. 7, 1986 - C.S. File 62/31-4

Found - Haines 1" T Iron protruding about 12" ground, firmly set bent and partially covered by decaying long. Haines map M 18-33, shows finding a 1" iron pipe. We were unable to locate this monument at or near the "T" iron. I checked with Mr. Haines who checked back through his notes. He provided a copy showing the 1" I.P. at S.64°49'W., 61.23 ft. from his monument. We were not able to locate the iron pipe. (Haines copy of his note is filed in C.S. File 62/31)

No BTs were found at S.3°W., 79.2 ft. or S.38°E., 99.0 ft.

42" dia. Fir stump 6 ft. high with previously opened blaze (14" deep) scribing "¼S" and old axe notch visible. (see photos in C.S. File). A ring count places blaze at about 70 years prior to trees death. From Haines monument this tree bears N.88°W., 80.6 ft.

48" dia. Fir stump 4 ft. high with previously opened possible blaze bears N.10½°E., 68.7 ft. The apparent blaze has been burned out. No scribing, face, axe notch, or burled wood was located in the blaze. This stump has 3 axed notches on westerly edge.

The blazes on the two found trees were oriented toward Haines monument. (See photos)

To perpetuate this location as determined by Haines, WE SET a 1" x 30" Iron pipe with a brass cap mkd: "Douglas County Surveyors Office T23S E 1/4 S3 only R7W 1986". We place the (Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

found T Iron monument along northerly edge of brass cap.
New BTs- 7" D.Fir double blazed and scribed "¼ S3 CS BT"
 bears S.28½°W., 35.5 ft.
 9" W.Fir double blazed and scribed "¼ S3 CS BT"
 bears S.76°W., 45.2 ft.
 27" W.Fir double blazed and scribed "¼ S3 CS BT"
 bears N.46°W., 68.3 ft.
This position, according to M 18-33, is located on line
between W 1/4 sec. 2 and corner of secs. 3 and 2 on township
line.

Fd. Ok by Carl Sweeden, 2/2006 - M154-12