

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 540140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #456, Surveyed Aug 1961/Jan. 1962 (DCSO records Vol. 31 Page(s) 13083)

Point for the center ¼ sec. cor. of sec. 35, at intersection with the E. and W. center line.

Set an iron post 28" long, 2½" dia., 25" in the ground, with brass cap mkd. C ¼ S 35
1961

from which

A W.Fir 15" dia., bears N.61½°E., 183 lks. dist. mkd. C ¼ S35 BT.

A W.Fir 18" dia., bears N.26½°W., 106 lks. dist. mkd. C ¼ S35 BT.

Mark Smalley - For: Roseburg Forest Products - Nov. 7, 1996
- C.S. 65/15 -7C

Mon. Fd.- 1961 BLM I.P.B.C.

Bt's Fd.- 48" W.Fir, N.61½°E., 183 lks.
39" W.Fir, N.26½°W., 106 lks.

New Accessories -

15" Fir, N.61°W., 6.1' scribed "C ¼ BT"

12" Fir, N.14°W., 43.7' scribed "C ¼ BT"

Found OK by M. Smalley, Sept. 2002 - M141-7