

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2524)

Set Fir post for the ¼ sec. cor., from which
A Fir 20" dia., bears N.60°E., 26 lks.
A Fir 12" dia., bears S.42°E., 15 lks.

Claude Kerr, Eng. #2125 - Corner report filed March 1949 - C.S. File 40/190

Found the 20" Fir and the scribe.
Set 2" x 2 ft. hazel stake for ¼ corner.

Wilford N. Haines, #239 - For: E.G. Whipple Mill and Mt. Baldey Lumber Co. - June 1959 to June 1961 - M 22-4

Set 1" x 1" x 36" T. iron. Original BTs. down.
Scribed - 55" Fir, North 131.7 ft.

David Edwards - For: Roseburg Resources Co - 4/2006 - M150-27

Found - 60" Fir north 131.7'
New BT- 17" Fir S.29°W., 14.33'
Set - 6' steel post 2' east.