

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2527)

Set Hazel post for the ¼ sec. cor., from which
A Maple 12" dia., bears N.72°E., 44 lks. dist.
A Maple 6" dia., bears S.15°W., 47 lks. dist.

Wilford N. Haines, #239 - For: E.G. Whipple Mill - Jan. 15, 1959 - M 13-64

Found old BT.
Set lot marker 1" x 1" x 36" Iron rod with brass cap inscribed: "Survey Point Wilford N. Haines #239".

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Dec. 1965 - C.S. File 52/125-24

Found - Haines T Iron.
Orig. 6" now 18" Maple S.20°W., 31.0 ft., recorded as S.15°W. Opened shows "T". Open higher and find BT scribe, reversed.
Orig. 12" now 22" Maple N.72°E., 29.0 ft., down lying almost on face. Did not open.
"T" Iron apparently set by distance intersection.
New BTs- 11" W.Fir S.14°W., 24.7 ft. mkd. ¼ S14 CS BT.
5" W.Fir N.24°W., 5.5 ft. mkd. ¼ S11 CS BT.
This corner lies on steep, NW. slope.

Douglas McMahan - For: Paul Zolezzi - 6/2023 - M182-39

Found - T-Iron (Haines)
36" D.Fir bears S.60°W., 7.4'
Record BTs (Not located this survey) - 1965
11" W.Fir bears S.14°W., 24.7'
5" W.Fir bears N.24°W., 5.5'