

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2528)

Marked small Fir 12" dia., for the ¼ sec. cor., from which
A Fir 12" dia., bears N.30°E., 18 lks. dist.
A Fir 12" dia., bears S.75°E., 15 lks. dist.

John M. Phillips - Snellstrom Lumber Co. - March 29, 1958 - C.S. File 42/350

This corner set by computation as recommended by Berlin in his letter of July 18, 1957. (1" iron pipe with brass cap furnished by DCSO)
(Copy of letter and other information in C.S. File)

Wilford N. Haines, #239 - For: E.G. Whipple Mill - Filed Jan. 15, 1959 - M 11-25

Found - 12" Fir, S.75°E., 15 lks.
Set Lot marker 1" x 1" x 36" T Iron with cap inscribed "Survey Point - Wilford N. Haines #239", from which scribed:
10" I.Cedar S.32°E., 16.0 ft.
12" Fir N.64°W., 20.5 ft.

Carl Sweeden - For: Rocking "C" Ranch & Robert Whipple - 2/2006 - M154-12 (Filed 9/2007)

Found - 1" x 1" Haines "T" iron bent over excavated to vertical point to identify true position and drove 5/8"x30" I rod w/Red plastic cap "SWEEDEN LS 2752" along side, BTs & evidence as follows:
Original 12" Fir S.75°E., 15 lks gone
10" I.Cedar S.32°E. 16.0', gone, slight depression at measured position
Original 12" fir N.64°W., 20.5', gone
New BTs- 9" D.Fir BT, N.25°E., 36.10', "S¼ S2 BT" & TAG
13" D.Fir BT, N.64°W., 13.00', "S¼ S2 BT" & TAG
8" D.Fir BT, S.70°W., 27.50', "N¼ S11 BT" & TAG
6" D.Fir BT, S.85°W., 12.10', "N¼ S11 BT" & TAG

Dan Baker - For: Rocking "C" Ranch - 12/2014 - M169-13

FOUND - 5/8" iron rod with red plastic cap "SWEEDEN PLS 2752" PER M154- 12
12" Fir, N.24°E., 36.1' to spike a t side/center - M154- 12 BT.

continued next page

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" Fir, N.87°E., 12.5' to spike at side/center -
M154-12 BT (rec bearing S.85°W., Per survey &
N.85°W., per tag)
12" Fir, S.70°W., 27.4' to spike at side/center -
M154-12 BT
17" Fir, N.63°W., 13.0' - to spike in side/center -
M154-12 BT

Douglas McMahan - For: Paul Zolezzi - 6/2023 - M182-39

Found - A 5/8" iron rod with red plastic cap drove down the
side of T- Iron per M154-12
14' D.Fir bears N.64°W., 13.0'
10" D.Fir bears S.70°W., 27.5'
Record BTs(not located this survey) 2007
9" D.Fir, bears N.25°(E)., 36.10'
6" D.Fir, bears S.85°W., 12.10'