

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New -	A 29 D.Fir stump with a healed face bears N.46°W., 29.4 ft. (record N.48¾°W. 46 lks) I scribe "¼ S36 BT" on a 29" D.Fir bears N.77°E., 56.5 ft.
Douglas Co. Surveyors Office - Stephen J Flause - Mike Koch - July 30, 2014 - C.S. File 67/41-34 -----	
Found -	A 3¼" dia., (1961 BLM) brass cap (properly mkd) on a 2" I.D. iron pipe set plumb and protruding approx. 14" from a now mostly buried, rough mound of stone.
OBTs -	A cedar 16" dia., now a fallen, broken and rotted 20+" dia., cedar with no discernible blazes or root-hole lies on ground near record B & D. A fir 16" dia., now a 33" dia., 2 ft. tall, tin covered fir stump with a partially open blaze, showing no scribing; bears S.80°W., 14.5 ft. (as per rec.)
1961/62 - BLM	A Fir 6" dia., now a shattered and rotted 14" dia., 3 ft. tall D.fir stump with a possible low healed blaze; bears S.28¼°E., 22.4 ft. (as per rec.)
	A fir 37" dia., now a 28" dia., 4 ft. tall, tin covered, fir stump with fully healed blaze; bears N.48¾°W., 30.4 ft. (as per rec.)
1994 -	A 29" D.Fir now a 32" dia., 5 ft. tall D.Fir stump with a partially healed single blaze showing the scribing "3 BT"; bears N.77°E., 57.3 ft. (Rec. N.77°E., 56.5 ft.)
New -	A 12" dia., D.Fir scribed "¼ S35 CS" "BT" on a double blaze; bears N.43½°W., 35.0 ft. An 8" dia., D.Fir scribed "¼ S35" "CSBT" on a double blaze; bears N.11½°W., 19.4 ft.
Note -	Monument is on moderate south slope just east of a N-S cutting line with older fir reprod to west and a recent clear-cut to east. Compass decl. 15½°E.