

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2517)

Set Cedar post for the cor. to secs. 25, 26, 35 and 36, from which

- A Fir 10" dia., bears N.48°E., 24 lks. dist.
- A Fir 30" dia., bears S.55°E., 39 lks. dist.
- A Fir 16" dia., bears S.30°W., 43 lks. dist.
- A Fir 6" dia., bears N.6°W., 23 lks. dist.

Claude Kerr, Eng. #2125 - Corner report filed March 1949 - C.S. File 40/190

Found - Fir BT, now 36", S.55°E., 39 lks.
18" windfall Fir with old marks.
Rest of BTs destroyed by old fire.
Set 4" x 4 ft. Cedar stake for the corner.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #456, Surveyed Aug 1961/Jan. 1962 (DCSO records Vol. 31 Page(s) 13072-73)

The Sec. Cor., determined at record bearing and distance from the only remaining original bearing tree:

- A Fir 45" dia., bears S.30°W., 43 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T 23 S R 7 W
S 26 | S 25
S 35 | S 36
1961

from which

- A Cedar 15" dia., bears N.66¼°E., 42 lks. dist. mkd. T23S R7W S25 BT.
- A Cedar 9" dia., bears S.49 3/4°E., 49 lks. dist. mkd. T23S R7W S36 BT.
- A Fir 26" dia., bears N.1°W., 44 lks. dist. mkd. T23S R7W S26 BT.

Fd. OK, Jan. 1994 by C. Mulkins - M 118-61
Fd. 4 BTs & BC by D. Edwards 4/2006 - M150-27