

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2519)

-----  
Set Laurel post for the ¼ sec. cor., from which  
A Laurel 14" dia., bears East, 12 lks.  
An Oak 20" dia., bears S.45°W., 47 lks.

Wilford N. Haines, #239 - For: E. G. Whipple Mill and Mt. Baldy Lumber Co. - June 1959 to June 1961 - M 22-4

-----  
Set 1" x 1" x 36" T. Iron, from which  
Orig. Oak BT, down.  
Scribed a 30" Fir, N.51°W., 32.1 ft.  
54" I.Cedar N.04°E., 12.0 ft.

Bruce Shaner - Nov. 2000 - C. S. File 65/33-11

-----  
Found - 1"x1" T iron, from which  
36" D.Fir BT, bark scribes visible, bears N.51°W.,  
32.1 ft. to center of tree.  
60" I.Cedar BT, face overgrown, bears N.4°E., 12.0  
ft. to center of tree.  
Set - 2½" Alum. cap on a ¾" x 40" iron rod over the  
1"x1" T iron, mkd: ROSEBURG RESOURCES CO.  
¼  
S 23|S 24  
RLS 430 2000  
6 ft. steel fence post, bears North, 1.0 ft.  
6 ft. steel fence post, bears South, 1.0 ft.