

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2521)

Marked a Fir 5" dia., for the ¼ sec. cor., from which
A Maple 12" dia., bears S.18°E., 33 lks.
A Fir 36" dia., bears S.20°W., 59 lks.

Wilford N. Haines, #239 - For: E.G. Whipple of Drain - May 9, 1957 - M 5-20

Found original corner.
Set 1" x 1" x 36" T. Iron rod with brass cap inscribed "Survey Point Wilford N. Haines #239".

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - July 1962 - C.S. File 52/125-4 (Added more information, previously just recorded as a "Fd. OK" 7/11/2022)

Reported as found OK
Found - Haines' "T" iron & cap.
Also fd. 2½" iron pipe extending 30" above ground
Maple stump (now 32" dia.) S.18°E., 21.8 ft. Old axe mks & old face, no scribing fd.
Badly burned remnants of old Fir stump S.20°W., 38.9 ft. too far gone to find scars or scribing.
No new BTs fd.

Douglas McMahan - For: Paul Zolezzi - 9/2022 - M181-33A (and 6/2023 M182-39)

Found - T-iron with brass cap
BTs (Record field verified)
15" D.Fir bears S.52°E., 21.1' with healed face
25" Fir bears N.42°W., 13.0' with healed face
16" Fir bears N.33°W., 20.0' with healed face