TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2520)

Set Cedar post for the ¼ sec. cor., from which
A Fir 36" dia., bears N.10°W., 50 lks.
A Fir 30" dia., bears S.10°W., 20 lks.

Survey by Bruce Shaner -For: Mt. Baldy Lumber Co. - April and May 1962 - M 23-62

Found nothing. Set 2" Angle Iron 36" long, from which a:
14" Yew bears S.50½°W., 71.5 ft. scribed "¼S BT".
14" W.Fir bears N.65°E., 21.6 ft. scribed "¼S BT".

Fd. OK, Nov. 1982 by D. Baker - M 93-23

Bruce Shaner - Nov. 2000 - C. S. File 65/33-14

Found - 2" "∠" iron, from which a:
20" Yew BT, scribes visible bears S.50½°W., 71.5 ft.
18" W.Fir BT now rotten stump bears N.65°E. 21.6 ft.
6 ft. steel fence post bears West, 1.0 ft.

Set - 2½" Alum. cap on a 3/4" x 40" iron rod over the 2" "∠" iron, mkd: ROSEBURG RESOURCES CO.
¼ S 13 / S 24
RLS 430 2000
12" D.Fir BT, I scribed "¼ S13 BT" bears N.6°E., 28.8 ft.