

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 6 Page(s) 2521-22)

Set Fir post for the ¼ sec. cor., from which
A Fir 8" dia., bears N.15°E., 30 lks. dist.
A Maple 12" dia., bears S.15°W., 41 lks.

Wilford N. Haines, #239 - For: E.G. Whipple of Drain - May 9, 1957 - M 5-20

Found both orig. BTs and R. Cedar corner tree.
Set 1"x1" x 36" iron rod with brass cap, N.78°31'W., 2.56 ft.

Dan Baker - For: Rocking "C" Ranch - 12/2014 - M169-13

Found - 17" Cedar snag corner tree
1"x1" "T" iron with 1" brass disk "HAINES 239" PER M5-20 bears N.70°W., (Record N.78°31'W.), 2.56' from corner tree (record iron rod & brass cap)
Marked BTs from "T" iron and not corner tree
41" cedar, N.8°E., 7.9' to spike at side/center, scribed "¼ S1 BT"
19" hemlock, S.29°E., 23.6' to spike at side/center, scribed "¼ S12 BT"
11" Fir, S.18°W., 54.0' to spike at side/center, scribed "¼ S12 BT"
47" cedar, N.56°W., 7.4' to spike at side/center, scribed "¼ S1 BT"