

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 1 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1495)

-----  
Set standard ¼ sec. post, from which  
A Cedar 24" dia., bears S.20°W., 78 lks. dist.  
A Cedar 18" dia., bears S.40°E., 125 lks. dist.

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan 22, 1881 (DCSO records Vol. 4 Page(s) 1534-35)

-----  
Set Chinquapin post for ¼ sec. cor. from which a  
Fir tree, 40" dia., bears N.88°E., 50 lks. dist.  
Fir tree, 10" dia., bears N.89°W., 10 lks. dist.

Wilford N. Haines - For: E.G. Whipple Mill - 1958 - M 11-25 and Field book H-197

-----  
Set Lot Marker 1"x1"x36" T Iron with cap inscribed.  
Scribed -32" Fir S.46°W., 44.5 ft.  
20" Fir S.01°E., 70.5 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C Putnam, crew - April/May 1962 - C.S. File 52/14-16

-----  
Found - Haines T Iron and cap.  
Haines 28" D.Fir S.46°W., 44.2 ft., bark scribed ¼  
S1 CC 363 BT.  
22" D.Fir S.2°E., 59.5 ft., bark scribed ¼ S1 CC 363  
BT.

Survey by Ken Hoffine - For: Lone Rock Timber - Feb. 1994 - C.S. File 63/154-5

-----  
Found - Haines T-Iron 1.5 ft. above ground.  
30" D.Fir stump bears S.2°E., 69.5 ft. No marks,  
(rec. S.1°E., 70.5 ft.)  
10" D.Fir bears S.21°E., 14.3 ft. I scribe BT and  
tag tree.  
Ground on steep south slope approximately 40 ft. north of  
shallow bowl like head of draw. Clearcut to west of corner.