

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 646700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 36 only, T22-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1469)

-----  
Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground, for standard  $\frac{1}{4}$  sec. cor. marked S C  $\frac{1}{4}$  S on the N. face; from which

A Fir 6" dia., bears N.84°E., 32 lks. dist. mkd. S C  $\frac{1}{4}$  S BT.

A Fir 12" dia., bears S.40°W., 12 lks. dist. mkd. S C  $\frac{1}{4}$  S BT.

This cor. is on the SE slope of spur, 150 ft. above creek.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12634)

-----  
The standard  $\frac{1}{4}$  sec. cor. of sec. 36 only, determined at record bearing and distance from the remains of one of the original bearing trees:

A Fir stump 14" dia., bears N.84°W., 32 lks. dist. mkd. S4.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 30" in the ground, with brass cap mkd:

T 22 S R 7 W

S C

$\frac{1}{4}$  S 36

1956

from which

A Fir 10" dia., bears N.41°E., 47 lks. dist. mkd.  $\frac{1}{4}$  S36 SC BT.

A Fir 14" dia., bears N.8°W., 54 lks. dist. mkd.  $\frac{1}{4}$  S36 SC BT.

Fd. OK, 1958, W. Haines, M 11-25 and F.B. H-197

Fd. OK, Feb. 1994, K. Hoffine, C.S. File 63/154-5